


PRODUCT SPECIFICATION



PRODUCT NUMBER: 1243A4T
DESCRIPTION: 12 SIS/AWM 3173/3237

DIAMETER: 0.148
TOLERANCE +/-: 0.003

GAUGE: 12
CONDUCTORS: 1
STRANDING: 65/30 TC
INSULATION: XLPE
VOLTAGE: 600V DC/1000V DC
TEMPERATURE: 125C
STYLE: SIS/AWM/3173/3237
PRINT LEGEND: E520012 12 AWG (3.31mm²) UL SIS 600V
or 3173 125C 600V or 3237 1000V --
301259 CSA CL1251 125C 600V or AWM I
A/B 125C 600V FT2



NOM WALL: 0.030
MINIMUM WALL: 0.027

NOTES: 1. Insulating material tested to rate -40C

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
09/24/2024	2		MIN TEMP