

PRODUCT SPECIFICATION



PRODUCT NUMBER: 1432A4T

DESCRIPTION: 14 1569


DIAMETER: 0.103

TOLERANCE +/-: 0.003

GAUGE: 14 AWG
CONDUCTORS: 1
STRANDING: 41/30 TC LHL
INSULATION: PVC
VOLTAGE: 300V DC
TEMPERATURE: 105 C
STYLE: 1569/TR-64

PRINT LEGEND: E511593 14 AWG (2.08mm²) UR AWM
1569 105C OR 1581 80C 300V VW-1 --
301259 CSA TR64 90C FT1 or AWM I A/B
105C 300V FT1

NOTES: 1. Insulating material tested to rate -40C



NOM WALL: 0.015

MINIMUM WALL: 0.013

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
09/24/2024	2		New Specification MIN TEMP