

# PRODUCT SPECIFICATION



PRODUCT NUMBER: 1433A1B

DESCRIPTION: 14 1015

DIAMETER: 0.126

TOLERANCE +/-: 0.003

GAUGE: 14 AWG

CONDUCTORS: 1

STRANDING: Solid Bare Copper

INSULATION: PVC


VOLTAGE: 600V DC/1000V DC

TEMPERATURE: 105 C

STYLE: 1011/1015/1230/1335/1032/TEW

PRINT LEGEND: E511593 14 AWG (2.08mm<sup>2</sup>) UR AWM  
1011/1015/1230/1335 105C 600V or 1032  
90C 1000V MOISTURE RESISTANT VW-1 --  
301259 CSA TEW 105C 600V FT1 or AWM I  
A/B 105C 600V FT1

NOTES: 1. Insulating material tested to rate -40C



NOM WALL: 0.030

MINIMUM WALL: 0.027

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
09/24/2024	3		Update OD MIN TEMP