


PRODUCT SPECIFICATION



PRODUCT NUMBER: 1632A4T
DESCRIPTION: 16 1007/1569

DIAMETER: 0.089
TOLERANCE +/-: 0.003

GAUGE: 16 AWG
CONDUCTORS: 1
STRANDING: 26/30 TC LHL
INSULATION: PVC
VOLTAGE: 300V DC
TEMPERATURE: 80/105 C
STYLE: 1569/1007/TR-64
PRINT LEGEND: E511593 16 AWG (1.31mm²) UR AWM
1569 105C or 1007 80C 300V VW-1 --
301259 CSA TR-64 90C FT1 or AWM I A/B
105C 300V FT1



NOM WALL: 0.015
MINIMUM WALL: 0.013

NOTES: 1. Insulating material tested to rate -40C

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
09/24/2024	2		New Specification MIN TEMP