

PRODUCT SPECIFICATION



DESCRIPTION: 20 MTW/1015

DIAMETER: 0.095

TOLERANCE +/-: 0.003

PRODUCT NUMBER: 2033A4T

GAUGE: 20 AWG

STRANDING: 10/30 TC LHL

INSULATION: PVC

VOLTAGE: 600V DC/1000V DC

TEMPERATURE: 105 C

STYLE: MTW/1011/1015/1230/1335/1032/
TEW



NOM WALL: 0.030

MINIMUM WALL: 0.027

PRINT LEGEND: E516147 20 AWG (0.519mm²) (UL) MTW or
AWM 1011/1015/1230/1335 105C 600V or
1032 1000V MOISTURE RESISTANT VW-1 --
301259 CSA TEW 105C 600V FT1 or AWM I
A/B 105C 600V FT1

NOTES: 1. Min Temp Rating: -40C

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
08/17/2020	1		New Specification