

# PRODUCT SPECIFICATION



DESCRIPTION: 22 1007/1569

DIAMETER: 0.061

TOLERANCE +/-: 0.003

PRODUCT NUMBER: 2232A4B

GAUGE: 22 AWG

STRANDING: 7/0096 BC LHL

INSULATION: PVC

VOLTAGE: 300V DC

TEMPERATURE: 80/105 C

STYLE: 1569/1007/TR-64



NOM WALL: 0.015

MINIMUM WALL: 0.013

PRINT LEGEND: E511593 22 AWG (0.324mm<sup>2</sup>) UR AWM  
1569 105C or 1007 80C 300V VW-1 --  
301259 CSA TR-64 90C FT1 or AWM I A/B  
105C 300V FT1

NOTES: Description only change on stranding.  
Product is still manufactured the same as it  
as always been.

Tolerances unless otherwise noted: FRACTIONS +/- 1/32, DECIMALS +/- 0.03 (2PL) +/-0.005 (3PL)

Confidential: This drawing and its information are the exclusive and confidential property of Sequel Wire and Cable, LLC and are not to be disclosed, duplicated, distributed, or otherwise used without the written consent of Sequel Wire and Cable, LLC. All rights reserved.

Date	Revision	ECN	Description
03/06/2023	2		updated copper description for operation clarification